


## Plywood panel

The mainstay of the range for all types of van bodyworks and dryfreight containers.

### PANOLIT



Plywood core coated on both sides  
with glass fibre reinforced  
polyester resin

#### Thicknesses and weights

THICKNESS in mm	6	11	14	17	20	23	27	30
Weight kg/m2 <b>CPR</b>	5,5	9,0	9,4	11,2	12,7	14,3	18,5	20,5
Weight kg/m2 <b>CPRFR</b>	-	-	9,4	11,2	12,7	14,3	-	-
Weight kg/m2 <b>CPRS</b>	-	-	9,7	11,5	13,0	14,7	-	-
Weight kg/m2 <b>CPRSR</b>	-	-	10,4	12,2	13,7	15,3	-	-

#### Advantages :

Good quality/price ratio, easy to assemble, easy to repair.

#### Types/Glass reinforcement :

CPR : 670g/m2                      CPRFR : 750g/m2  
CPRS : 930g/m2                    CPRSR : 1700g/m2

#### Dimensions :

Standard height : 2440mm  
Maximum height : 3150mm  
Special sizes : upon request.

Standard length : up to 13550 mm

#### Upon specific request:

Colour gelcoat outside face.  
Special cut according to drawings and doors size.  
Inserts according to drawings .  
Panels protected with plastic film upon request.  
Panels with peel ply, anti-slipping coat to realize floors.  
Rebates.

**Applications :** van bodywork and dryfreight containers., doors without tubes, concrete shuttering , shelters for animals...

