

Plywood panel

The mainstay of the range for all types of van bodyworks and dryfreight containers.

PANOLIT



Plywood core coated on both sides
with glass fibre reinforced
polyester resin

Thicknesses and weights

THICKNESS in mm	6	11	14	17	20	24	27	30
Weight kg/m2 CPR*	5,5	9,0	9,4	11,2	12,7	16,2	18,5	20,5
Weight kg/m2 CPRFR	-	-	9,4	11,2	12,7	16,2	-	-
Weight kg/m2 CPRS	-	-	9,7	11,5	13,0	16,5	-	-
Weight kg/m2 CPRSR	-	-	10,4	12,2	13,7	17,2	-	-
Weight kg/m2 BOR45*	-	-	-	-	17,0	-	-	-
Weight kg/m2 BORSR	-	-	-	-	18,0	-	-	-

*** Panels with CPR- prefix: pine core panels with BOR- prefix: birch core**

Advantages :

Good quality/price ratio, easy to assemble, easy to repair.

Types/Glass reinforcement :

CPR : 630g/m2

CPRFR : 730g/m2

CPRP : 830g/m2

CPRS : 930g/m2

CPRSR : 1710g/m2

BOR45 : 930g/m2

BORSR : 1710g/m2

Dimensions :

Standard height : 2440mm

Standard length : up to 13550 mm

Maximum height : 3150mm

Special sizes : upon request.

Upon specific request :

Colour gelcoat outside face.

Special cut according to drawings and doors size.

Inserts according to drawings .

Panels protected with plastic film upon request.

Rebates.

Applications : van bodywork and dryfreight containers., doors without tubes, concrete shuttering , shelters for animals...

